



LP 3028/3033

LASER PRINTER

LP 3028/3033

TECHNICAL DATA

LP 3028/3033

POWER PACKAGE WITH VERSATILITY

The UTAX LP 3028 and LP 3033 present themselves as productive but compact with impressive speeds of 28 and 33 pages per minute respectively. The standard 500 sheet universal cassette comfortably deals with higher volume print tasks. Boasting brilliant 1.200 x 1.200 dpi, they are convincing all-rounders used standalone or in a network environment. Thanks to several optional enhancements the UTAX laser printers cope powerfully with all tasks.

TECHNOLOGY

| | |
|------------------|--|
| Type | Laser printer with internal controller |
| Print technology | Electrophotographic laser b/w |
| Print speed | LP 3028: up to 28 pages DIN A4 per minute in b/w LP 3033: up to 33 pages DIN A4 per minute in b/w |
| | 1. page after approx. 9,5/11,5 seconds |
| Resolution | 1.200 dpi (1.200 x 1.200 dpi) |

HARDWARE/SOFTWARE CHARACTERISTICS

| | |
|-----------|---|
| Processor | PowerPC 750CX/300 MHz |
| Memory | LP 3028: 64 MB (max. 320 MB/1 DIMM slot) LP 3033: 96 MB (max. 576 MB/2 DIMM slots) |
| Emulation | PCL6, PostScript 3 (KPD L 3) |

INTERFACE

| | |
|--------------------|---|
| Standard interface | USB 2.0, IEEE 1284 parallel, 10/100BaseTX |
|--------------------|---|

PAPER MANAGEMENT

| | |
|-----------------------|--|
| Standard paper supply | Max. 500 sheet universal cassette, max. 100 sheet multi bypass |
| Optional paper supply | 3 x 500 sheet universal cassette, 1 x 2.000 sheet large paper deck (only LP 3033) 60-105 g/m ² , DIN A4, DIN A5, DIN B5, letter, legal, custom |
| Standard paper output | Max. 250 sheet face-down |
| Optional paper output | Max. 250 sheet face-up (max. 100 sheet with optional duplex unit), |
| Paper formats | DIN A4, DIN A5, DIN B5, letter, legal, custom |
| Paper weights | Universal cassette: 60-105 g/m ² , multi bypass: 60-200 g/m ² |
| Print media | Universal cassette: 60-105 g/m ² normal and recycling paper, multi bypass: 60-200 g/m ² normal and recycling paper, transparency*, label*, envelope* |

DIMENSIONS/WEIGHT

| | |
|-------------------|---|
| Dimensions/weight | 345 x 390 x 300 mm (W x D x H), approx. 13 kg |
|-------------------|---|

ENVIRONMENT

| | |
|-------------------|--|
| Power supply | 220/240 V, 50/60 Hz, max. 4,0 A |
| Power consumption | LP 3028: approx. 425 W operation/13 W sleep mode LP 3033: approx. 521 W operation/13 W sleep mode |
| Noise level | LP 3028: 55 dB operation/33 dB stand-by mode LP 3033: 57 dB operation/36 dB stand-by mode |
| Certificates | GS/TÜV, CE |

CONSUMABLES

| | |
|------------------------|---|
| Toner kit LP 3028/3033 | Microfine toner black for 20.000 pages DIN A4 with 5% coverage (starter kit for 10.000 pages DIN A4 with 5% coverage) |
|------------------------|---|

OPTIONS

| | |
|-------|---|
| PF-60 | 500 sheet universal cassette, 60-105 g/m ² , DIN A4, DIN A5, DIN B5, letter, legal, custom, max. 3 pieces PF-60 |
| PF-8E | 2.000 sheet large paper deck, 60-200 g/m ² DIN A4, DIN A5, DIN B5, letter, legal, custom (only LP 3033) |
| PB-60 | Printer base, necessary for use of PF-8E (only LP 3033) |
| DU-61 | Duplex unit, 60-105 g/m ² , DIN A4, DIN A5, DIN B5, letter, legal, custom |
| EF-60 | Envelope feeder, max. 70 normal/100 airmail envelopes DIN A6-DIN C5* |
| SO-60 | Sorter/5-bin Mailbox, max. 1.000 sheet face-down (5 x 200 sheet) |
| PT-4 | Paper output tray, max. 250 sheet face-up, |
| PT-60 | Paper output tray, max. 100 sheet face-up (when duplex unit DU-61 is installed) |



The LP 3028 and the LP 3033 are manufactured in accordance with the requirements of the ENERGY STAR Program of the US Environmental Agency. Specifications subject to change without notice (03/2004). UTAX recommends to use only genuine UTAX accessories for trouble-free operation of your machine. *for recommended print media refer to the user manual