

GENERAL

Type	Desktop
Function	Copy, print, scan, optional: fax
Print technology	Laser colour and b/w
Original format	max A4 from platen glass
Original feeder	75 sheet A4 (standard, with auto reversing function), A6R-A4, 50-120 g/m ² (simplex/duplex), banner: 915 mm length, A4 width
Copy/print speed	max 30 A4 pages/min, duplex: max 30 A4 pages/min in colour and b/w
1st page	Colour: 8 seconds, b/w: 7 seconds (print)*; colour: 7.8 seconds, b/w: 6.4 seconds (copy)*
Warm-up time	20 seconds*
Copy resolution	max 600 x 600 dpi
Greyscales	256
Paper feed	1 x 500 sheet universal cassette (A6R-A4), 100 sheet multi-bypass (A6R-A4 (min 70 x 148 mm, max 216 x 356 mm))
Paper weights	Universal cassette 60-220 g/m ² , multi-bypass 60-220 g/m ² , duplex 60-220 g/m ²
Paper output	500 sheet A4
System memory	1,536 GB RAM, (max 3,072 GB RAM), 32/128 GB SSD**
Continuous copying	1-999 copies
Zoom	25 %-400 % in steps of 1 %
Functions	Adjustable colour touch screen (7 inch), duplex, job reservation, job programs, continuous scan, skip blank pages, N-up, quiet mode (half speed mode), login by function, 100 management codes

DIMENSIONS/WEIGHT

Dimensions	736.6 x 550 x 507.5 mm (H x W x D; with original feeder)
Weight	approx. 49.6 kg (with original feeder)

ENVIRONMENT

Mains voltage	220/240 V, 50 Hz
Power consumption	approx. 1,317 W max, approx. 497 W in operation, approx. 69 W in stand-by mode, approx. 0.5 W in sleep mode, TEC value: 0.42 kWh/week
Noise level	approx. 50.1 dB(A)/49.9 in operation (colour / b/w-mode), stand-by mode: immeasurable (ISO 7779/9296)
Safety	GS/TÜV, CE

PRINT SYSTEM

Type	Integrated within the system
Print format	A6R-A4
Print resolution	600 x 600 dpi, 1200 x 1200 dpi (reduced speed)
Processor	ARM Cortex-A9 Dual core 1.2 GHz und ARM Cortex-M3 100MHz
Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2)
Network protocols	TCP/IP, Net BEUI
Operating systems	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare**, Linux, Mac OS 10.9
Emulations	PCL6 (PCL 5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS
Functions	Colour Optimiser, USB direct printing, PDF/XPS direct printing, printing of e-mails, private printing, quiet mode (half speed mode), barcode printing, Mobile Print (Android/iOS)/Apple AirPrint, Google Cloud Print, Wi-Fi

SCAN SYSTEM

Scan type	CCD colour and b/w
Scan format	max A4
Scan speed	b/w: max 40/17 A4 images/min (simplex/duplex) with 300 dpi, colour: max 30/13 A4 images/min (simplex/duplex) with 300 dpi
Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi
Scan mode	Photo, text, photo/text, optimised for OCR
File types	TIFF, JPEG, XPS, PDF, high compression PDF, encrypted PDF, XPS, OpenXPS, text-searchable PDF**
Interfaces	10/100/1000BaseTX, USB 2.0
Network protocol	TCP/IP
Operating systems	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019
Functions	Scan to SMB, Scan to e-mail, Scan to FTP, Scan to USB, TWAIN scan, WSD scan, SMTP authentication, LDAP

FAX SYSTEM (11)

Compatibility	Super G3
Original format	max A4
Modem speed	33.6 kbps
Transmission speed	3 seconds or less using JBIG
Compression method	JBIG, MMR, MR, MH
Fax resolution	max. 400 x 400 dpi
Fax memory	8 MB (3.5 MB image memory)

FAX SYSTEM (11)

Abbreviated dial	200 numbers
One touch dial	100 numbers
Group dial	50 numbers
Operating systems	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019
Functions	Network fax driver, automatic redialling, delayed transmission

OPTIONS

Finisher	DF-5100 internal finisher (capacity: 300 sheet A4, stapling max 50 sheet A4), MT-5100 multi tray (500 sheet + 5 x 100 sheet A4; cannot be combined with DF-5100/J5-5100)
Job separator	J5-5100 (capacity: 100 sheet A4)
Paper feed	PF-5120 (1 x 500 sheet universal cassette [A6R-A4]), PF-5130 (2 x 500 sheet universal cassettes [A6R-A4]), PF-5140 (2,000 sheet large capacity tray [A4]); 1 x PF-5120 is required for installation of PF-5130 or PF-5140!
Other options	Data Security Kit (E)***, Card Authentication Kit (B), Card reader holder (11), Scan Extension Kit (A)****, UG-33 ThinPrint® Kit, IB-53 Gigabit Ethernet card, IB-35/IB-54 WLAN card, HD-6 SSD (32 GB), HD-7 SSD (128 GB), DT-5100 document tray, cabinet no. 74 (high), cabinet no. 75 (low)

* Depending on operating status.

** optional

*** when using HD-6 or HD-7 the Data Security Kit can be activated free of charge

**** additional memory required

To enable HyPAS functionality additional memory is required.

Specifications subject to change without notice.

Image shows machine with optional accessories.

UTAX has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialised in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of TA Triumph-Adler GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.



HyPAS™



Your UTAX-dealer