

352ci / 402ci / 502ci

TECHNICAL DATA

IF IT WORKS, IT'S
UTAX

GENERAL	
Type	Desktop
Function	Copy, print, scan, optional: fax
Print technology	Laser colour and b/w
Original format	max A4 from platen glass
Copy/print speed	352ci: max 35 A4 pages/min, duplex: max 35 A4 pages/min in colour and b/w; 402ci: max 40 A4 pages/min, duplex: max 40 A4 pages/min in colour and b/w; 502ci: max 50 A4 pages/min, duplex: max 50 A4 pages/min in colour and b/w
1st page	352ci: colour: 6.5 seconds, b/w: 5.5 seconds (print)*; colour: 7.3 seconds, b/w: 5.9 seconds (copy)*; 402ci: colour: 6.4 seconds, b/w: 5.4 seconds (print)*; colour: 6.9 seconds, b/w: 5.8 seconds (copy)*; 502ci: colour: 6.4 seconds, b/w: 5.4 seconds (print)*; colour: 6.2 seconds, b/w: 5.3 seconds (copy)*
Warm-up time	24 seconds*
Copy resolution	max 600 x 600 dpi
Greyscales	256
Paper feed	1 x 500 sheet universal cassette (A6R-A4), 100 sheet multi-bypass (A6R-A4 (min 70 x 148 mm, max 216 x 356 mm), Banner: max 216 mm width x 1,220 mm length)
Paper weights	Universal cassette 60-220 g/m ² , multi-bypass 60-220 g/m ² , duplex 60-220 g/m ² , Banner 129-163 g/m ²
Paper output	500 sheet A4
System memory	352ci: 4 GB RAM, 16 GB SSD + 320 GB HD** 402ci/502ci: 4 GB RAM, 8 GB SSD + 320 GB HD
Continuous copying	1-9,999 copies
Zoom	25 %-400 % in steps of 1 %
Functions	Adjustable colour touch screen (7 inch), duplex, job reservation, job programs, continuous scan, skip blank pages, N-up, quiet mode (half speed mode), login by function, 1,000 management codes, encryption/overwriting of hard disk data (Data Security Kit and Trusted Platform Module)

DIMENSIONS/WEIGHT	
Dimensions	352ci: 612.8 x 550 x 508 mm (H x W x D; without original feeder) 402ci/502ci: 612.8 x 550 x 550 mm (H x W x D; without original feeder)
Weight	352ci: approx. 47.4 kg (without original feeder) 402ci/502ci: approx. 49.3 kg (without original feeder)

ENVIRONMENT	
Mains voltage	220/240 V, 50 Hz
Power consumption	352ci: approx. 1,338 W max, approx. 563 W in operation, approx. 81 W in stand-by mode, approx. 0.7 W in sleep mode, TEC value: 0.50 KWh/week 402ci: approx. 1,404 W max, approx. 652 W in operation, approx. 84 W in stand-by mode, approx. 0.7 W in sleep mode, TEC value: 0.55 KWh/week 502ci: approx. 1,426 W max, approx. 750 W in operation, approx. 90 W in stand-by mode, approx. 0.7 W in sleep mode, TEC value: 0.67 KWh/week
Noise level	352ci: approx. 51.2 dB(A)/50.7 dB(A) in operation (colour / b/w-mode), stand-by mode: immeasurable (ISO 7779/9296); 402ci: approx. 52.0 dB(A)/51.4 dB(A) in operation (colour / b/w-mode), stand-by mode: immeasurable (ISO 7779/9296); 502ci: approx. 54.6 dB(A)/54.2 dB(A) in operation (colour / b/w-mode), stand-by mode: immeasurable (ISO 7779/9296);
Safety	GS/TÜV, CE

PRINT SYSTEM	
Type	Integrated within the system
Print format	A6R-A4
Print resolution	600 x 600 dpi, 1,200 x 1,200 dpi (reduced speed)
Processor	Freescall QorIQ T1024 (Dual Core) 1.0 GHz
Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (3), NFC
Network protocols	TCP/IP, Net BEUI
Operating systems	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare**, Linux, Mac os X 10.9
Emulations	PCL6 (PCL 5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS
Functions	Colour Optimiser, USB direct printing, PDF/XPS direct printing, printing of e-mails, private printing, quiet mode (half speed mode), barcode printing, Mobile Print (Android/iOS)/Apple AirPrint, Google Cloud Print, NFC, Wi-Fi**

SCAN SYSTEM	
Scan type	CCD colour and b/w
Scan format	max A4
Scan speed	b/w: max 85/170 A4 images/min (simplex/duplex) with 300 dpi, colour: max 65/130 A4 images/min (simplex/duplex) with 300 dpi (DP-5130); b/w: max 60/120 A4 images/min (simplex/duplex) with 300 dpi, colour: max 60/120 A4 images/min (simplex/duplex) with 300 dpi (DP-5120)*
Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi
Scan mode	Photo, text, photo/text, optimised for OCR
File types	TIFF, JPEG, XPS, PDF, high compression PDF, encrypted PDF, XPS, OpenXPS, text-searchable PDF**
Interfaces	10/100/1000BaseTX, USB 2.0
Network protocol	TCP/IP
Operating systems	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019

SCAN SYSTEM	
Functions	Scan to SMB, Scan to e-mail, Scan to FTP, Scan to USB, TWAIN scan, WSD scan, SMTP authentication, LDAP
OPTIONAL FAX SYSTEM (10X)	
Compatibility	Super G3
Original format	max A4
Modem speed	33.6 kbps
Transmission speed	3 seconds or less using JBIG
Compression method	JBIG, MMR, MR, MH
Fax resolution	max 600 x 600 dpi
Fax memory	170 MB
Abbreviated dial	2,000 numbers
One touch dial	1,000 numbers
Group dial	500 numbers
Operating systems	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019
Functions	Network fax driver, automatic redialling, delayed transmission

OPTIONS	
Original feeder	DP-5100 document processor with automatic reverse function (A6R-A4, banner paper up to 1,900 mm (length), capacity: 75 sheet A4, paper weight 50-120 g/m ²); DP-5120 document processor with simultaneous duplex scanning (A6R-A4, banner paper up to 1,900 mm (length), capacity: 100 sheet A4, paper weight 50-120 g/m ²); DP-5130 document processor with simultaneous duplex scanning, double feed and staple detection sensors (A6R-A4, banner paper up to 1,900 mm (length), capacity: 270 sheet A4, paper weight 50-120 g/m ²)
Finisher	DF-5100 internal finisher (capacity: 300 sheet A4, stapling max 50 sheet A4), DF-5110 (capacity: 1,000 sheet A4, stapling max 50 sheet A4), DF-5120 (capacity: 3,200 sheet A4, stapling max 50 sheet A4, manual stapling also available, 2-/4-hole punching), PH-5110 hole punch unit for DF-5110 (2-/4-hole punching), MT-5100 multi tray (500 sheet + 5 x 100 sheet A4; cannot be combined with DF-5100/DF-5110/DF-5120/JS-5100)
Job separator	JS-5100 (capacity: 100 sheet A4)
Paper feed	PF-5120 (1 x 500 sheet universal cassette (A6R-A4)), PF-5130 (2 x 500 sheet universal cassettes (A6R-A4)), PF-5140 (2,000 sheet large capacity tray (A4)); 1 x PF-5120 is required for installation of PF-5130 or PF-5140!
Other options	Card authentication kit (B), Card reader holder (11), Scan Extension Kit (A), UG-33 ThinPrint® kit, UG-34 Emulation Option Kit, IB-53 Gigabit Ethernet card, IB-35/IB-54 WLAN card, HD-11(B) (320 GB, optional for 352ci only), Internet Fax Kit (A), NK-7100(B) numeric key pad, DT-5100 document tray, cabinet no. 74 (high), cabinet no. 75 (low)

* abhängig vom Betriebszustand

** optional

Änderungen in Ausstattung und Konstruktion vorbehalten.

Abbildungen mit optionalem Zubehör

UTAX has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialised in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of TA Triumph-Adler GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.



Your UTAX-dealer