

3263i / 4063i

TECHNICAL DATA

IF IT WORKS, IT'S



GENERAL	
Type	Desktop
Function	Copy, print, scan, optional: fax
Print technology	Laser b/w
Original format	max A3 from platen glass
Copy/print speed	3263i: max 32 A4 pages/min and max 17 A3 pages/min 4063i: max 40 A4 pages/min and max 21 A3 pages/min
1st page (Copy/Print)	4.3/4.9 seconds* (3263i), 3.6/4.2 seconds* (4063i)
Warm-up time	18 seconds*
Copy resolution	600 x 600 dpi
Greyscales	256
Paper feed	2 x 500 sheet universal cassettes (A5R-A3), 100 sheet multi-bypass (A6R-A3)
Paper weights	Universal cassette 60-163 g/m ² , multi-bypass 45-256 g/m ² , duplex 60-163 g/m ²
Paper output	upper tray 50 sheets A4 lower tray 250 sheets A4
System memory	4 GB RAM, 32 GB SSD**/ optional: 320 GB or 1 TB HDD**
Continuous copying	1-9,999 copies
Zoom	25 %-400 % in steps of 1 %
Functions	Adjustable resistive colour touch screen (10.1 inch), duplex, 1,000 management codes, skip blank pages, encryption/overwriting of hard disk data (Data Security Kit), secure boot, run time integrity check, S/MIME, SIEM etc
DIMENSIONS/WEIGHT	
Dimensions	683 x 594 x 696 mm (H x W x D)
Weight	approx. 59 kg
ENVIRONMENT	
Main voltage	220/240 V, 50/60 Hz
Power consumption	approx. 1,620 W max, approx. 510 W (3263i)/600 W (4063i) in operation, approx. 100 W in stand-by mode, approx. 0.5 W in sleep mode, TEC value: 0.40/0.53 kWh/ week (3263i/4063i)
Noise level	3263i: approx. 46.9 dB(A) in operation, stand-by mode: 37.5 dB(A) (ISO 7779/9296) 4063i: approx. 48.7 dB(A) in operation, stand-by mode: 36.4 dB(A) (ISO 7779/9296)
Safety	GS/TÜV, CE

PRINT SYSTEM	
Type	Integrated within the system
Print format	A6R-A3
Print resolution	1,200 x 1,200 dpi, 600 x 600 dpi
Processor	ARM A53 1.6 GHz
Interfaces	USB 3.0, USB-Host(4), Gigabit-Ethernet (10/100/1000BaseTX), SD-Card Slot
Network protocols	TCP/IP, Net BEUI
Operating systems	Windows 8.1/10, Windows Server 2012/2012 R2/2016/2019, Novell NetWare***, Linux, Mac OS 10.9, Chrome OS
Emulations	PCL6 (5e, XL), KPD L 3 (PostScript 3 compatible), XPS, PDF 2.0, PRESCRIBE IIe
Functions	USB direct printing, PDF/XPS direct printing, super resolution imaging (only with KX driver), SNMPv3, printing of e-mails, private printing, EcoPrint, barcode printing, Mobile Print (Android/iOS)/Apple AirPrint, NFC, Wi-Fi Direct***
SCAN SYSTEM	
Scan type	CCD colour and b/w
Scan format	max A3
Scan speed	max 100 (simplex) or 200 (duplex) A4 originals/min in colour and b/w with DP-7170 (300 dpi)
Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi
Scan mode	Photo, text, photo/text, optimised for OCR
File types	TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS, Open XPS
Interface	10/100/1000BaseTX
Network protocol	TCP/IP
Operating systems	Windows 8.1/10, Windows Server 2012/2012 R2/2016/2019
Functions	Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP, multiple cropping, handwriting enhancement
OPTIONAL FAX SYSTEM 12	
Compatibility	Super G3
Original format	max A3
Modem speed	33.6 kbps
Transmission speed	3 seconds or less using JBIG
Compression method	JBIG, MMR, MR, MH
Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi
Fax memory	170 MB
Abbreviated dial	2,000 numbers
One touch dial	1,000 numbers
Group dial	500 numbers
Operating systems	Windows 8.1/10, Windows Server 2012/2012 R2/2016/2019
Functions	Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception

OPTIONS	
Original feeder	DP-7140 document processor with automatic reverse function (A5R-A3, capacity: 50 sheet A4, paper weight 45-160 g/m ²), DP-7150 document processor with automatic reverse function (A6R-A3, capacity: 140 sheet A4, paper weight 35-160 g/m ²), DP-7160 document processor with simultaneous duplex scanning (A6R-A3, capacity: 320 sheet A4, paper weight 35-220 g/m ²), DP-7170 document processor with simultaneous duplex scanning, multi-feed detection and staple detection (A6R-A3, capacity: 320 sheet A4, paper weight 35-220 g/m ²)
Platen cover	Platen cover type E (if document processor is not installed)
Finisher	DF-7120 (capacity: 1,000 sheet A4, stapling max 50 sheet A4), DF-791 (capacity: 3,000 sheet A4, stapling max 65 sheet A4), PH-7C hole punch unit for DF-7120/DF-791, MT-730 (B) multi tray for DF-791
Paper feed	PF-791 (2 x 500 sheet universal cassettes (A5R-A3)), PF-B10 (2 x 1,500 sheet large capacity cassette (A4))
Other options	Scan extension kit (A), Internet fax kit (A), Card authentication kit(B), Keyboard holder 10, Banner guide 10, UG-33 ThinPrint® kit, UG-34 Emulation option kit, IB-53 Gigabit Ethernet card, IB-54 WLAN card (IEEE802.11a/b/g/n/ac), IB-37 WLAN card (IEEE802.11a/b/g/n/ ac, Wi-Fi direct) or IB-38 WLAN**** card (IEEE 802.11 b/g/n Wi-Fi direct), DT-730 (B) Document tray, NK-7120 Numeric Keyboard (10 keys), cabinet no. 70, HD-15 (320 GB HDD**), HD-16 (1 TB HDD**)
* Depending on operating status	
** für Copy, Print, Scan, Fax	
*** optional	

Specifications subject to change without notice.

Image shows machine with optional accessories.

UTAX has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialised in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of TA Triumph-Adler GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.



HyPAS

