

Technical Data:

5059i • 6059i • 7059i

GENERAL

Type	Desktop
Function	Copy, print, scan, optional: fax
Print technology	Laser b/w
Original format	max A3
Copy/print speed	5059i: max 50 A4 pages/min and max 25 A3 pages/min 6059i: max 60 A4 pages/min and max 30 A3 pages/min 7059i: max 70 A4 pages/min and max 35 A3 pages/min
1st page (Print/Copy)	4.3/3.7 seconds ¹ (5059i), 3.8/3.4 seconds ¹ (6059i), 3.8/3.3 seconds ¹ (7059i)
Warm-up time	17 seconds ²
Copy resolution	600 x 600 dpi
Greyscales	256
Paper feed	2 x 500 sheet universal cassettes (cassette 1: A6R-A4, cassette 2: A6R-SRA3 [320 x 450 mm]), 150 sheet multi-bypass (A6R-SRA3, Banner [305 x 1,219 mm]), SRA3 and banner only for printing
Paper weights	Universal cassette 52-300 g/m ² , multi-bypass 52-300 g/m ² , duplex 64-256 g/m ²
Paper output	500 sheet A4
System memory	4 GB RAM, 128 GB SSD/optional: 320 GB or 1 TB HDD**
Continuous copying	1-9,999 copies
Zoom	25 %-400 % in steps of 1 %
Functions	Adjustable colour touch screen (10.1 inch), duplex, 1,000 management codes, skip blank pages, motion sensor, encryption/overwriting of hard disk data (Data Security Kit), trusted platform module (TPM), secure boot und runtime integrity check, simple certificate enrollment protocol (SCEP), TLS 1.3, OCSP, CRL, S/MIME, SIEM-Support, Allowlisting, fax server connectivity etc.

DIMENSIONS/WEIGHT

Dimensions	790 x 602 x 665 mm (H x W x D)
Weight	approx. 83 kg

ENVIRONMENT

Mains voltage	220/240 V, 50/60 Hz
Power consumption	approx. 1,750 W max, approx. 660/770/850 W in operation (5059i/6059i/7059i), approx. 40 W in stand-by mode, approx. 0.5 W in sleep mode, TEC value: 0.6/0.78/0.95 kWh/week (5059i/6059i/7059i)
Noise level	5059i/6059i/7059i: approx. 52.5/54.1/54.8 dB(A) in operation (b/w-mode), stand-by mode: 30.9/32.8/31.6 dB(A) (ISO 7779/9296)
Safety	GS/TÜV, CE

PRINT SYSTEM

Type	Integrated within the system
Print format	A6R-SRA3
Print resolution	600 x 600 dpi, max 1,200 x 1,200 dpi
Processor	ARM A53 1.6GHz
Interfaces	USB 3.0, USB-Host(4), Gigabit-Ethernet (10/100/1000BaseTX), SD-Card Slot
Network protocols	TCP/IP, Net BEUI
Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac OS 10.14
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PDF 2.0, PRESCRIBE IIe
Functions	USB direct printing, PDF/XPS direct printing, super resolution imaging (only KX driver), SNMPv3, printing of e-mails, private printing, EcoPrint, barcode printing, Mobile Print (Android/iOS)/Apple AirPrint, NFC, Wi-Fi Direct ³

SCAN SYSTEM

Scan type	CCD colour and b/w
Scan format	max A3
Scan speed	max 137 (simplex) or 274 (duplex) A4 originals/min in colour and b/w with DP-7170 (300 dpi)
Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi
Scan mode	Photo, text, photo/text, optimised for OCR
File types	TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS, Open XPS
Interface	10/100/1000BaseTX
Network protocol	TCP/IP
Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022
Functions	Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP, multi crop scan, handwriting enhancement, document guard, cloud capture functionality, image defect prevention, ID-scan

OPTIONAL FAX SYSTEM 14

Compatibility	Super G3
Original format	max A3
Modem speed	33.6 kbps
Transmission speed	3 seconds or less using JBIG
Compression method	JBIG, MMR, MR, MH
Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi
Fax memory	170 MB
Abbreviated dial	2,000 numbers

One touch dial	1,000 numbers
Group dial	500 numbers
Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022
Functions	Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception

OPTIONS

Original feeder	DP-7150 document processor with automatic reverse function (A6R-A3, capacity: 140 sheet A4, paper weight 35-160 g/m ²), DP-7160 document processor with simultaneous duplex scanning (A6R-A3, capacity: 320 sheet A4, paper weight 35-220 g/m ²), DP-7170 document processor with simultaneous duplex scanning, multi-feed detection and sensor with staple detection (A6R-A3, capacity: 320 sheet A4, paper weight 35-220 g/m ²)
Platen cover	Platen cover type E (if document processor is not installed)
Finisher	DF-7100 internal finisher (capacity: 500 sheet A4, stapling max 50 sheet A4, not available for 7059i), DF-7120 (capacity: 1,000 sheet A4, stapling max 50 sheet A4), DF-7140 (capacity: 4,000 sheet A4, stapling max 65 sheet A4), DF-7150 (capacity: 4,000 sheet A4, stapling max 100 sheet A4), PH-7120 hole punch unit for DF-7100, PH-7C hole punch unit for DF-7120/7140/7150, BF-730 brochure module for DF-7140 (max 20 sheet saddle stitching and folding A4/A3, tri-folding max 5 sheet A4), BF-9100 brochure module for DF-7150 (max 20 sheet saddle stitching and folding A4/SRA3, tri-folding max 5 sheet A4), MT-730 (B) multi tray for DF-7140, IS-7100 Inserter (available for 6059i/7059i), ZF-7100 Z-fold unit (available for 6059i/7059i)
Job separator	JS-7100 (100 sheet, 52-300 g/m ² , A6R - SRA3), JS-7110 inner shift tray (250 sheet, 52-300 g/m ² , A6R - SRA3)
Paper feed	PF-7140 (2 x 500 sheet universal cassettes [A5R-SRA3]), PF-7150 (2 x 1,500 sheet large capacity cassette [A4]), PF-7120 (3,000 sheet large capacity tray [A4]), side deck)
Other options	Scan extension kit (A), Internet fax kit (A), Card authentication kit(B), Keyboard holder 10, Banner guide 10, UG-33 ThinPrint® kit, UG-34 Emulation option kit, IB-53 Gigabit Ethernet card, IB-54 WLAN card (IEEE802.11b/g/n, Wi-Fi direct, WPA3), IB-37 WLAN card (IEEE802.11a/b/g/n/ac, Wi-Fi direct) or IB-38 WLAN card (IEEE 802.11 b/g/n Wi-Fi direct), DT-730 (B) Document tray, NK-7120 Numeric Keyboard (10 keys), cabinet no. 81, HD-15 (320 GB HDD ²), HD-16 (1 TB HDD ²)

- ¹ Depending on operating status
- ² For copy, print, scan, fax
- ³ optional
- ⁴ IB-38 is only available for selected countries outside the EU that do not support the IB-37








To enable HyPAS functionality additional memory is required. Specifications subject to change without notice. Image shows machine with optional accessories.

About UTAX: UTAX is a registered trademark of the TA Triumph-Adler GmbH. The Hamburg-based company specialises in the sale of high-quality printing and copying systems. The broad product portfolio includes hardware as well as software applications. In addition to copying, printing and multifunctional systems (MFP) for the office workplace, UTAX supplies customised IT solutions and services as well as comprehensive consulting for efficient document processes in companies. In Germany, the UTAX brand is distributed through a network of over 200 authorised dealers. Internationally, the company operates in over 40 countries in the EMEA region.

IF IT WORX, IT'S

UTAX

utax.com