

Technical data: 7515ci • 8515ci • 9515ci

GENERAL		DIMENSIONS/WEIGHT		FUNCTIONS	
Type	Console Unit	Dimensions	Standard: 1,227 x 685 x 660 mm (H x W x D) With Copy Tray Typ D ³ : 1,227 x 1,019 x 660 mm (H x W x D)	Functions	Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP, multi crop scan, handwriting enhancement, document guard, cloud capture functionality, image defect prevention, ID-scan, OCR text recognition
Function	Copy, print, scan, optional: fax	Weight	approx. 165 kg	OPTIONAL FAX SYSTEM 14	
Print technology	Laser colour and b/w	ENVIRONMENT		Compatibility	Super G3
Original format	max A3 from platen glass	Mains voltage	220/240 V, 50/60 Hz	Original format	max A3
Original feeder	Dual scanner with straight-path function for special media, including ultrasonic sensor for multi-feed detection + staple detection sensor (A6R-A3, capacity: 500 sheet A4 (80g/m ²), banners up to 2,200mm, paper weight 35-220 g/m ² [simplex], 50-220 g/m ² [duplex]) Straight-path function: 50 sheet (80g/m ²) paper weight (35-500 g/m ²), custom formats from 53,98mm - 297mm (width) and 85.6mm - 432mm (length)	Power consumption	approx. 2,400 W max, approx. 1,200/1,320/1,260 W in operation (7515ci/8515ci/9515ci), approx. 130 W in stand-by mode, approx. 0.5 W in sleep mode, TEC value: 1.45/1.62/1.79 kWh/week (7515ci/8515ci/9515ci)	Modem speed	33.6 kbps
Copy/print speed	7515ci: max 70 A4 pages/min and max 35 A3 pages/min in colour and max 75 A4 pages/min and max 37 A3 pages/min in b/w, 8515ci: max 75 A4 pages/min and max 37 A3 pages/min in colour and max 85 A4 pages/min and max 42 A3 pages/min in b/w 9515ci: max 80 A4 pages/min and max 40 A3 pages/min in colour and max 95 A4 pages/min and max 47 A3 pages/min in b/w	Noise level	7515ci/8515ci/9515ci: approx. 54.7/54.9/55.1 dB(A) in operation colour mode, 55.7/55.6/55.8 dB(A) in operation mono mode, standby mode: 37.8/37.8/45.2 dB(A) (ISO 7779/9296)	Transmission speed	3 seconds or less using JBIG
1st page (Copy/Print)	7515ci: Colour: 5.5/5.0 seconds ¹ , b/w: 4.1/3.7 seconds ¹ 8515ci: Colour: 5.5/5.0 seconds ¹ , b/w: 4.1/3.7 seconds ¹ 9515ci: Colour: 5.5/5.0 seconds ¹ , b/w: 4.1/3.7 seconds ¹	Safety	GS/TÜV, CE	Compression method	JBIG, MMR, MR, MH
Warm-up time	45 seconds ¹ (7515ci) 60 seconds ¹ (8515ci/9515ci)	PRINT SYSTEM		Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi
Copy resolution	600 x 600 dpi	Type	Integrated within the system	Fax memory	170 MB
Greyscales	256	Print format	A6R-SRA3	Abbreviated dial	2,000 numbers
Paper feed	1 x 550 sheet universal cassettes (A6R-SRA3 [max 330.2 x 457 mm]), 1 x 550 sheet universal cassettes (A6R-SRA3 [max 330.2 x 487 mm]), 2 x 1,500 sheet large capacity cassette (A4), 250 sheet multi-bypass (A6R-SRA3, Banner [330.2 x 1,219 mm])	Print resolution	max 2,400 x 2,400 dpi	One touch dial	1,000 numbers
Paper weights	Universal cassette 52-300 g/m ² , large capacity cassette 52-300 g/m ² , multi-bypass 52-300 g/m ² , duplex 52-256 g/m ²	Processor	QorIQ LS1046A (Quad Core) 1.6 GHz	Group dial	500 numbers
Paper output	250 sheet A4 (upper tray) and 100 sheet A4 (lower tray) with Copy tray type D ³ , 70 sheet A4 (right tray)	Interfaces	USB 3.0, USB 2.0-Host(4), Gigabit-Ethernet (10/100/1000BaseTX), SD-Card-Slot, NFC	Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022
System memory	9 GB RAM, 256 GB SSD ¹	Page description language	PRESCRIBE	Functions	Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception
Continuous copying	1-9,999 copies	Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ab OS 10.14	OPTIONS	
Zoom	25 %-400 % in steps of 1 %	Emulations	PCL6 (Sc, XL), KPDL 3 (PostScript 3 compatible), XPS, OpenXPS, PDF, PPML, XJDF/XJMF	Finisher	DF-7200 (capacity: 4,000 sheet A4, stapling max 65 sheet A4), DF-7210 (capacity: 4,000 sheet A4, stapling max 100 sheet A4), PH-7220 hole punch unit for DF-7200 and DF-7210, BF-7200 brochure module for DF-7200/DF-7210 (max 20 sheet saddle stitching and folding A4/SRA3, tri-folding max 5 sheet A4), MT-7200 (B) Multi tray for DF-7200/DF-7210, IS-7200 inserter (compatible with DF-7200/DF-7210), ZF-7200 Z-fold unit (compatible with DF-7200/DF-7210)
Functions	Adjustable colour touch screen (10.1 inch), duplex, 1,000 management codes, skip blank pages, motion sensor, encryption/overwriting of hard disk data (Data Security Kit), trusted platform module (TPM), secure boot und runtime integrity check, simple certificate enrollment protocol (SCEP), TLS 1.3, OCSP, CRL, S/MIME, SIEM-Support, Allowlisting, fax server connectivity etc	Functions	USB direct printing, PDF/XPS direct printing, super resolution imaging (only KX driver), SNMPv3, printing of e-mails, private printing, EcoPrint, barcode printing, Mobile Print (Android/iOS)/Apple AirPrint, NFC, Wi-Fi Direct ³	Paper feed	PF-7210 (3,200 sheet large capacity tray [A6R-SRA3], side deck), PF-7200 (3,000 sheet large capacity tray [A4], side deck)
		SCAN SYSTEM		Professional colour management	Fiery® Controller (Printing System 18 depends on Printing System Interface Kit 18)
		Scan type	CCD and CIS colour and b/w	Other options	Internet fax kit (A), Card authentication kit(B), Keyboard holder 10, Banner guide 12, UG-33 ThinPrint® kit, UG-34 Emulation option kit, IB-53 Gigabit Ethernet card, IB-54 WLAN card (2.4/5 GHz IEEE802.11/b/g/n, Wi-Fi direct, WPA3), IB-55 WLAN card (2.4GHz, IEEE802.11/b/g/n, Wi-Fi direct, WPA3), IB-37 WLAN card (2.4/5 GHz, IEEE802.11a/b/g/n/ ac, Wi-Fi direct) or IB-38 WLAN card (2.4 GHz IEEE 802.11 b/g/n Wi-Fi direct), Copy Tray Typ D, DT-730 (B) Document tray, NK-7120(B) Numeric Keyboard (10 keys), HD-16 (1 TB HDD)
		Scan format	max A3	¹ Depending on operating status	
		Scan speed	max 150/300 (simplex/duplex) A4 originals/min in colour and b/w (300 dpi)	² For copy, print, scan, fax	
		Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi, (1,200 x 1,200 dpi TWAIN Driver)	³ optional	
		Scan mode	Photo, text, photo/text, OCR	⁴ IB-38/IB-55 is only available for selected countries outside the EU	
		File types	TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS, Open XPS, Microsoft office formats		
		Interfaces	10/100/1000BaseTX		
		Network protocol	TCP/IP		
		Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022		








To enable HyPAS functionality additional memory is required.

Specifications subject to change without notice.

Image shows machine with optional accessories.

About UTAX: UTAX is a registered trademark of the TA Triumph-Adler GmbH. The Hamburg-based company specialises in the sale of high-quality printing and copying systems. The broad product portfolio includes hardware as well as software applications. In addition to copying, printing and multifunctional systems (MFP) for the office workplace, UTAX supplies customised IT solutions and services as well as comprehensive consulting for efficient document processes in companies. In Germany, the UTAX brand is distributed through a network of over 200 authorised dealers. Internationally, the company operates in over 40 countries in the EMEA region.

IF IT WORX, IT'S

UTAX

utax.com

04/2026