

Technical Data:

P-3523DW • P-4021DN • P-4021DW

GENERAL		DIMENSIONS/WEIGHT		OPTIONS	
Type	Desktop	Dimensions (H x W x D)	272 x 375 x 393 mm	Paper feed	max 2x PF-1100 (250 sheet universal cassette [A6-A4, 60-163 g/m ²])
Function	Print	Weight	approx. 14 kg	Other options	Card authentication kit (B), UG-33 ThinPrint® kit, UG-50 Trusted Platform Module, cabinet no. 78
Print technology	Laser b/w	ENVIRONMENT			
Print speed	P-3523DW: max 35 A4 pages/min, duplex: max 18 pages/min P-4021DN/P-4021DW: max 40 A4 pages/min, duplex: max 20 A4 pages/min	Mains voltage	220/240 V, 50(60 Hz)		
1st page¹	6.4 sec	Power consumption	P-3523DW: approx. 1,085 W max, approx. 481 W in operation, approx. 6 W in stand-by mode, approx. 0.3 W in sleep mode, TEC value: 0.3 KWh/week P-4021DN/P-4021DW: approx. 1,085 W max, approx. 556 W in operation, approx. 6 W in stand-by mode, approx. 0.3 W in sleep mode, TEC value: 0.34 KWh/week		
Warm-up time	15 sec ¹	Noise level	approx. 52,1/ 51,6 / 51,6 dB(A) in operation, not measurable in stand-by mode (ISO 7779/9296)		
Greyscales	256	Safety	GS/TÜV, CE		
Paper feed	1 x 250 sheet universal cassette (A6R-A4), 100 sheet multi-bypass (A6R-A4 [min 70 x 148 mm, max 216 x 356 mm])	PRINT SYSTEM			
Paper weights	Universal cassette 60-163 g/m ² , multi-bypass 60-220 g/m ² , duplex 60-163 g/m ²	Type	Integrated within the system		
Paper output	250 sheets A4	Print format	A6R-A4		
System memory	512 MB RAM	Print resolution	600 x 600 dpi, max. 1,200 x 1,200 dpi		
Display	LCD display 128 x 64 dots, half size 21 characters x 5 lines with numeric keypad	Processor	ARM Cortex A53 single 1.0GHz + ARM Cortex-M3 100MHz		
Functions	Duplex, job reservation, job programs, 20 management codes, Secure Boot ³ , Runtime Integrity Check ³ , Simple Certificate Enrollment Protocol (SCEP), TLS 1.3, OCSP, CRL ⁴ , SIEM-Support etc.	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (1), SD-card slot, Wi-Fi ²		
		Network protocols	TCP/IP, Net BEUI		
		Operating systems	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9		
		Emulations	PCL6 (PCL 5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS		
		Functions	USB direct printing, PDF/XPS direct printing, printing of e-mails, private printing, quiet mode (half speed mode), barcode printing, Mobile Print (Android/iOS), Apple AirPrint, Universal print, Wi-Fi ²		

- ¹ depending on operating status.
² P-3523DW/P-4021DW
³ UG-50 Trusted Platform Module necessary
⁴ optional SD card required








To enable HyPAS functionality additional memory is required. Specifications subject to change without notice.
Image shows machine with optional accessories.

About UTAX: UTAX is a registered trademark of the TA Triumph-Adler GmbH. The Hamburg-based company specialises in the sale of high-quality printing and copying systems. The broad product portfolio includes hardware as well as software applications. In addition to copying, printing and multifunctional systems (MFP) for the office workplace, UTAX supplies customised IT solutions and services as well as comprehensive consulting for efficient document processes in companies. In Germany, the UTAX brand is distributed through a network of over 200 authorised dealers. Internationally, the company operates in over 40 countries in the EMEA region.

IF IT WORX, IT'S



utax.com