Umweltdatenblatt P-3523DW

Umweltmanagement	Die Fertigung dieses Geräts erfolgt in Produktionsstätten, die mit einem Umweltmanagementsystem gem. ISO 14001 arbeiten.
Umweltzertifikat	Blauer Engel nach DE-UZ 219

Leistungsaufnahme | Wärmeabgabe

	Leistungsaufnahme	Wärmeabgabe
Maximal (beim Einschalten, „inkl. Optionen"):		
	1085 W	3906 kJ/h
Drucken:	481 W	1732 kJ/h
Bereit:	6 W	22 kJ/h
Ruhemodus:	0,3 W	1,1 kJ/h
Schalter-Aus:	0,1 W	0,4 kJ/h

Typischer Stromverbrauch (TEC)	0,30 kWh/Woche (ermittelt gem. ENERGY STAR 3.2)
Aufstellhinweise	Der Drucker sollte so aufgestellt werden, dass sowohl seitlich, als auch vor und hinter dem System ausreichend Platz für die Bedienung und zur Wartung freigehalten wird. Für eine gute Belüftung sorgen. Das Druck-System nicht in staubigen Räumen aufstellen und vor Ammoniakdämpfen schützen. Bitte beachten Sie die Hinweise im Anwenderhandbuch.
Luftfeuchtigkeit	10% - 80%
Raumtemperatur	10°C - 32,5°C

Geräuschemission (gem. ISO 7779 / ISO 9296)

Surface sound pressure level
(Messung in 1m Entfernung, Durchschnitt aus Einzelmessungen)

Betrieb:	52,1 dB(A) L_{pA}
Bereit:	nicht messbar

Operator position (Messung in Bedienerposition)

Betrieb:	60,1 dB(A) L_{pA}
Bereit:	nicht messbar

Garantierter A-bewerteter Schallleistungspegel entsprechend DE-UZ 219

Betrieb:	67,6 dB(A) L_{WAc}

Garantierter A-bewerteter Schallleistungspegel in Anlehnung an DE-UZ 219

Bereit:	nicht messbar

Lichtquelle	Belichtung Trommel: Laser

Emissionen

nach DE-UZ 219

TVOC (Betrieb):	3,21 mg/h
TVOC (Bereit):	0,112 mg/h
Benzol:	< Bestimmungsgrenze
Styrol:	0,02 mg/h
Ozon:	0,57 mg/h
Staub:	< Bestimmungsgrenze

Irrtum und Änderungen vorbehalten

Environmental Data Sheet P-3523DW

Environmental Management	This device is manufactured in production facilities that work with an environmental management system in accordance with ISO 14001.
Environmental Label	Blue Angel DE-UZ 219

Power Consumption | Heat Emission

	Power Consumption	Heat Emission
Maximum (at switch on, full options):		
	1085 W	3906 kJ/h
Printing:	481 W	1732 kJ/h
Ready:	6 W	22 kJ/h
Sleep mode:	0.3 W	1.1 kJ/h
Off-mode:	0.1 W	0.4 kJ/h

TEC	0.30 kWh/week (determined according to ENERGY STAR 3.2)
Installation Notes	The unit should be placed in a way, that there is adequately space for operation and maintenance on both sides, as well as in front and behind the system. Provide adequate ventilation. Do not set up the unit in dusty rooms, and protect against ammonia vapours. Please follow the instructions in the user manual.
Humidity	10% - 80%
Room Temperature	10°C – 32.5°C

Noise Emission
(According to ISO 7779 / ISO 9296)

Surface sound pressure level
(Measurement in 1 m distance; average of single measurements)

Operation:	52.1 dB(A) L_{pA}
Ready:	not measurable

Operator position

Operation:	60.1 dB(A) L_{pA}
Ready:	not measurable

Declared A-weighed sound power level according to DE-UZ 219

Operation:	67.6 dB(A) L_{Wac}

Declared A-weighed sound power level following DE-UZ 219

Ready:	not measurable

Light Source	Exposure drum: Laser

Emissions

According to DE-UZ 219

TVOC (Operation):	3.21 mg/h
TVOC (Ready):	0.112 mg/h
Benzene:	< Limit of quantitation
Styrene:	0.02 mg/h
Ozone:	0.57 mg/h
Dust:	< Limit of detection

Effective: 10/2025
Errors and omissions excepted.